



**VIRTUAL COOPERATIVE NETWORK FORMED BY LOCAL
CLIENTS IN ZONES WITHOUT CELLULAR SERVICES**

5

Background Of The Invention

Field of the Invention

10

This invention generally relates to mobile communications, and more specifically, to a virtual cooperative network formed by mobile objects.

Prior Art

15

Mobile communication devices can lose the ability to receive and transmit signals when they are in certain locations. For example, when people are driving through a tunnel they lose radio transmission and communication via cell phone becomes impossible. The same situation happens when a user enters the underground metro or railway station.

20

One possible solution to this problem is to install a local transmission station inside the tunnel or underground in the metro area. This is not a particularly effective solution, however, because transmission stations are not installed everywhere, and moreover this solution would be very expensive. The majority of tunnels and metro stations do not have such equipment.

25

Summary Of The Invention

An object of this invention is to improve the transmission and reception capabilities of cellular devices.

30

Another object of the present invention is to provide a virtual network that allows cellular devices to transmit and receive in underground areas, such as in tunnels and subway stations.

- 5 Another object of the present invention is to provide emergency channels for sending emergency messages in areas where cellular providers cannot reach cellular telephones.

Another object of the invention is to define the density of cars by interchanging signals between neighboring cars.

10

Another object of the invention is to use additional chips embedded in E-Z passes for interchanging signals between cars.

15

These and other objectives are attained with a method and system for forming a virtual network. The method comprises the steps of providing each of a plurality of mobile objects with a transceiver, and transmitting a cellular/radio signals from a source. At least a first of the mobile objects is located in an area where the transceiver of the first mobile object does not receive the signal directly from the source, while a second of the mobile objects is in a position where the transceiver of the second mobile object receives the signal directly from the source. The transceiver of the second mobile object is used to receive the signal directly from the source and to transmit the signal to the transceiver of the first mobile object.

20

- Preferably, each of the mobile objects is provided with a sensor to determine when the transceivers of others of the mobile objects are not able to receive the cellular/radio signals directly from the source. When the sensor of one of the mobile objects determines that the transceiver of another of the mobile objects is not able to receive the signals directly from the source, the sensor of said one of the mobile objects activates the transceiver of said one of the mobile objects to transmit the signal to the transceiver of the other of the mobile object.

25

30

For example, a virtual network embodying the invention may be formed of cars inside a tunnel. The cars inside the tunnel will transmit the signal between each other. If cars are moving inside the tunnel that is not equipped with the local transmission station, every
5 car will start transmitting signals to the cars next to it. Each car in the chain becomes a transmitter or conductor of the signal. This chain of transmitting signals continues until it reaches the car outside the tunnel with a clear signal, that can be transmitted to the car inside the tunnel. This continues through all the cars inside of tunnel until the car moves out the tunnel.

10

The electronic equipment that transmits the signal can be done the same way as currently used optical toll payment systems such as those referred to as E-Z Pass. An additional chip can be embedded in the E-Z Pass or installed inside the car during the car
production by the car manufacture, allowing the car to receive and transmit a signal to
15 nearby cars. Such an electronic chip inside of the car can be used for other purposes such as remote diagnostics when the car has any problem. This could be another E-Z Pass function. It can also be used for determining the car density on the road for detecting traffic jams in certain areas. The denser the traffic, the greater is the congestion of cars, and the smaller the distance between the cars and their transmitters. When the cars are
20 close to each other, they can receive the weak signal from the neighboring car. An advantage of this is that there is no need to install a powerful transmitter inside of the car; a weak transmitter would suffice. Also, this electronic chip can transmit signals to a satellite to determine the traffic conditions in certain areas.

25 The opportunity to transmit signals from one car to another car can be used for multiple purposes. It may be a permanent device inside the car, and for example this electronic chip can be used for receiving and transmitting signals between cars inside tunnels, bridges or other areas, where it is not possible to receive signals from transmitting stations. It is important for people that are stopped in heavy traffic inside a tunnel to
30 have the ability to call and report the delay. This invention will allow them to transmit

the cell phone signal from one car to another until the signal gets outside the tunnel, where the signal can be successfully transmitted.

This invention also provides the ability, for instance, to check the stock market quotations by someone who is stopped inside a tunnel and who has a need to check the price quote. The same applies with placing a transaction over the cell phone. If the signal is very weak, they will not be able to communicate inside the tunnel. This invention allows this to be accomplished.

Further benefits and advantages of the invention will become apparent from a consideration of the following detailed description, given with reference to the accompanying drawings, which specify and show preferred embodiments of the invention.

Brief Description Of The Drawings

Figure 1 illustrates a virtual network formed of cars inside a tunnel.

Figure 2 shows a virtual network comprised of people in a tunnel.

Figure 3 shows a transceiver inside a car.

Figure 4 is a block diagram of an electronic transceiver chip that may be used in this invention.

Figure 5 illustrates how a signal can be transmitted into a tunnel.

Figure 6 is a flow chart outlining a preferred method for carrying out this invention.

Detailed Description Of The Preferred Embodiments

Figure 1 generally describes how the signal is transmitted from one car to another car. Number 100 is a tunnel, 101 is a cellular transmitting station that transmits the signal to car 102 that gets into the tunnel. Car 102 transmits the signal via antenna 103. All the signals that the car receives through its antenna get transmitted, via electronic chip 104, inside the tunnel to the car next to it (car 105). This is how the signal from outside the tunnel gets inside the tunnel. The receiving chip 104 on the car inside the tunnel will receive the signal. Now, the car inside the tunnel transmits the signal from electronic chip 104 to the car next to it, to its electronic chip 104 and so on. The car that receives the signal operates with the signal exactly the same way as it would as if it received the signal directly from the station 101; as if the car was outside the tunnel.

Figure 2 shows the case where, instead of vehicles, people are inside a tunnel or underground 200 in a metro station or other place with limited radio transmission. Transmission station 101 transmits the signal. 202 represents a person who is about to enter a tunnel. This person has a cellular phone 203 which still can receive the signal directly from transmission station 101. The cell phone 203 has an electronic chip 204 that is capable of transmitting a signal by itself for short distances. This signal gets sent from the cell phone 203 to a cell phone 205 with an electronic chip 204 that can receive the signal. The user with the cell phone 205 is inside the tunnel and cannot receive the signal directly from the transmitting station 101. The signal from this user with cell phone 205 gets transmitted to the next cell phone user who has a phone 206 with electronic chip (transceiver) 204 to receive the signal. Thus, all the signals get transmitted from the user outside the tunnel to the next user, through the chain of other users, using their cell phone transceiver chip to transmit the signal.

Figure 3 gives an example of how to use the transceiver inside the car. It will be used to determine traffic jams. 300 is the road with moving cars. 301 is the satellite 302, 303 etc. are the cars on the road equipped with the transceiver electronic devices 304, 305, 306

respectively. The transeiver device is allowed to transmit the signal on very short distances. The signal gets sent from the transeiver 304 and received by transeiver 305 and the distances are measured and sent to satellite 301. This information is sent from satellite 301 to computer 307, and on the computer screen 308, the picture shows the traffic for this particular region.

The example given here shows road 309 packed with cars that create a traffic jam. At the same time, the picture shows cars traveling freely along a road 310.

This information later gets transmitted to car drivers and tells them what streets in the city have traffic jams and shows them alternate roads. This also can be used to transmit information about how many people are in a particular city or region. For example, it would be possible to determine the number of people that show up at a demonstration, sports event or other gathering. By using a cell phone that people carry it is possible that the electronic transeiver chip can report how many people are located in one particular region.

Figure 4 is a block diagram of the electronic transeiver chip that is capable of receiving and transmitting a signal from one cell phone to another phone and from one car to another car. The cell phone 400, 401 antenna, 402 receiver that contains analyzer 406. Analyzer is capable of determining whether some of the received signals are required to be transmitted. It is possible to do this whether or not people subscribe to a particular service. For example, whether or not it is allowed to transmit a signal inside a tunnel. Only the signal that is marked to allow transmitting will be transmitted further. Analyzer 406 will check if the signal is marked for further transmission. Analyzer also checks whether the signal is marked as an "emergency signal." This can be in a case where there was a traffic accident in a tunnel or some driver in a tunnel had a cardiac attack. If the signal is marked as an "emergency signal," it will receive preferred treatment. It can be transmitted through a frequency band that is most widely available to other cellular devices. Under a special agreement, one can block other signals that are transmitted through this frequency band in order to allow the transmission of the emergency signals.

If transmission of the signal is allowed, the signal will be labeled and the frequency of the signal will be changed to transmitted via transmitted frequency from one cell phone to another. This special signal will be labeled by block 404 that this is a special signal
5 that has a secondary transmission from one cell phone to another cell phone. As the transmitter 405 will be transmitting the signal in special frequency selected for this service, it will not disturb a signal going on other frequencies. This signal will be marked as a second signal. Analyzer 406 will determine if the signal was issued directly or if it is the secondary signal that is transferred from one cell device to another cell device.

10

Analyzer 406 will transmit the secondary signal to block 407 to be descent to the next user. Block 407 will transmit a signal to the next cell user as a regular audio signal. The analyzer will understand this particular signal and descent to a particular user. The signal can be decoded with a special code that corresponds to a code of a particular cell phone
15 user. If the signal has a special code which is descent to a particular user, a signal will not be transmitted to other cars, or other cell user. If the code of the signal does not correspond to the code of this particular cell phone, then the signal will get transmitted further to the next available user and so on.

20 Figure 5 is a block diagram showing how the signal gets transmitted inside the tunnel. Device receives the signal 500. 501 checks whether the signal was received outside the tunnel or inside. If the signal was received outside the tunnel, the analyzer will check if it needs to transmit the signal inside the tunnel and how far from the tunnel it is located. The analyzer checks to see if it receives any signal from the cars inside the tunnel. Cars
25 inside the runnel will send weak signals outside the tunnel indicating that they need information or that they are trying to transmit. The cars outside the tunnel will receive the signal from the cars inside the tunnel indicating that there is a request for the transmission from the cars inside the tunnel. Block 502 checks whether there is a signal that has been received from inside the tunnel. The analyzer inside the transeiver checks
30 if the signal received has a special label identifying the secondary transmission. Also, it

checks if the signal is marked for the user that is subscribing to that particular service. Also it checks whether the signal is marked as the emergency signal.

After this is determined, block 505 transmits the signal in a determined frequency, and
5 the signal is marked as the secondary signal. Block 504 determines whether the signal
transmitted inside the tunnel will be transmitted to the car next to it unconditionally. If
the analyzer determines that the signal is labeled with the special code that is descent to
a particular car, it will not be transmitted any further. It also will enable a determination
of how many cars are currently inside the tunnel. This special signal will be sent from
10 the satellite to a car outside the tunnel and transmitted to each of the cars inside the
tunnel. The special signal marked with the special code will be used to compute the
distance between the cars and it will count how many cars are in the tunnel. The satellite
will receive the signal back which will help to determine to assess the number of cars in
the tunnel.

15
Figure 6 is a flow chart showing a procedure to determine traffic jams and the density of
the population during gatherings in certain areas. Block 600 sends the short range signal,
which is received by another device 601. If this device is outside the tunnel, it will send
a long range signal to a satellite that will determine its location. If this device was inside
20 the tunnel, the block 602 will send the short distance signal labeled as the signal to
determine the distance between the next user with cell phone or car with electronic
transceiver. This signal has the special purpose to determine the distance between the
cars in the tunnel and this is how the signal is labeled. Block 603 counts how many cars
received this signal. When the special signal gets transmitted from one car to another,
25 distance and count is computed; and once it reaches the car outside the tunnel, the signal
is redirected by this car to the satellite as the total information. A satellite computer can
compute the number of cars in the tunnel. It is also possible to have special devices on
the streets that will read the information from the electronic device inside the car and
transmit this information to a satellite. This will allow computing the number of cars in

certain locations. This also can be used for computing a density of people carrying or using cell phones.

5 While it is apparent that the invention herein disclosed is well calculated to fulfill the objects stated above, it will be appreciated that numerous modifications and embodiments may be devised by those skilled in the art, and it is intended that the appended claims cover all such modifications and embodiments as fall within the true spirit and scope of the present invention.

0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000